

SNACKY MAX



With a footprint of only 735 x 855 mm and 7 trays, SNAKKY MAX allows a complete refreshment service offering a choice of snacks, confectionery, cans and bottles.

As you would expect from Necta, the Snakky Max is the operator's dream, as replenishing stocks couldn't be simpler, with pull out trays which tilt to allow easy access. To ensure client satisfaction, the Snakky Max has a sensor in the delivery area which detects if a product has actually been vended (option).

Designed to sit alongside the similarly sized Kikko Max in order to provide a full refreshment service, Snakky Max can also be banked with Astro, working in master/slave mode, and with Zenith.

TEMPERATURE

Uniform (5-8°C)

Varied (10-15°C in upper trays and 5-7°C in lower trays) with operating conditions of 32°C.

ELECTRONIC CONTROL

- 16-bit electronic control with incorporated Flash EPROM
- Automatic setup and reading of statistics with Flash application or Up-Key
- Remote monitoring via GSM technology (with the specific kit)

PAYMENT SYSTEMS

The payment systems and the electronic board are located inside a separate compartment, with independent access and slide-out opening for complete extraction, allowing work to take place in this area without affecting the temperature inside the product compartment. Snakky Max is pre-set for the installation of systems with Executive and MDB protocol, as well as validators.

The following can be installed on the same machine:

- Change-giver coin mechanism/validator
- Bill validator
- Cashless system with key or card

ACCESSORIES

5 direct selection buttons (standard on some versions)

Vend detector system kit (standard on some versions)

Kit to block dispensing compartment (standard on some versions)

Coin box cover kit

Wall mounting bracket kit

RS232 jack kit

GSM kit



Example of possible configuration

EXAMPLE OF POSSIBLE CONFIGURATION

3 snack trays

15 selections / 219 products

1 bottle tray

6 selections / 36 products

3 can trays

18 selections / 108 products

13	13	13	13	13	13	13	140 mm
19	19	13	13	19	19	19	128 mm
13	13	13	13	13	13	13	130 mm
6	6	6	6	6	6	6	215 mm
6	6	6	6	6	6	6	112 mm
6	6	6	6	6	6	6	116 mm
6	6	6	6	6	6	6	116 mm

 Snacks
 Bottles 0.5 litre PET
 Cans 0.33/0.25 litre

The numbers in the table indicate the product capacity

CHARACTERISTICS	
Height	1830 mm*
Width	735 mm
Depth	855 mm
Depth with door open	1350 mm
Weight	225 Kg
Power supply voltage	230 V
Power supply frequency	50 Hz
Absorbed power	560 W
Maximum operating conditions	32°C - 65% R. H.
*+10 - 10 mm	

POWER CONSUMPTION	
For each hour of stand-by	266 Wh
Ambient temperature	20°C
Refrigerated box temperature	5°C



N&W GLOBAL VENDING S.p.A.

Via Roma, 24
24030 Valbrembo (BG) Italy
Ph. +39 035 606111 - Fax +39 035 606519

www.nwglobalvending.com